



**600 Series Deadbreak
T&B Catalog Number:**

UPC Number:
Status:
Description:

K655BLR
78378665669
Active

15/25kV 600 Series Deadbreak Elbow with Test Point Housing Only (with Stud)

Application

600 Series deadbreak elbows, straight receptacles, junctions, vault stretchers and accessories are used to connect equipment and cable on primary feeder and network circuits.

General

Temperature Range -40°C to 65°C

Technical Information

Test Point Yes

Specifications

Temperature Rating -40°C to 65°C

Notes

For 900-amp ratings, substitute 675 for 650 and 655; 676 for 656; K671 for K651; K675 for K650 and K655; K676 for K656; 775 for 750 and 755; 776 for 756 and 2X for 0X in the catalog number. The 900-amp rating requires cooper current-carrying connector components and copper conductor cable.
Available without the stud by adding "N" to the catalog number.
Available without the stud by adding "N" to the catalog number.

Certifications

RoHS Compliance No

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com