



**600 Series Deadbreak  
T&B Catalog Number:**



**UPC Number:**  
**Status:**  
**Description:**

650ETP  
78378662284  
Made to Order

15kV 600 Series Deadbreak Elbow Tap Plug

**Application**

600 Series deadbreak elbows, straight receptacles, junctions, vault stretchers and accessories are used to connect equipment and cable on primary feeder and network circuits.

**General**

Temperature Range -40°C to 65°C

**Technical Information**

Test Point No

**Specifications**

Temperature Rating -40°C to 65°C

**Notes**

For 900-amp ratings, substitute 675 for 650 and 655; 676 for 656; K671 for K651; K675 for K650 and K655; K676 for K656; 775 for 750 and 755; 776 for 756 and 2X for 0X in the catalog number. The 900-amp rating requires cooper current-carrying connector components and copper conductor cable. Available with the stud factory-assembled by adding "SP" to the catalog number. 675ETP, K675ETP and 775ETP are available as -SP only. The stud is not field removable.

Available with a loose stud by adding suffix "S" to the catalog number.

Use 600ATM Assembly Tool.

Use 600ATM Assembly Tool.

**Certifications**

RoHS Compliance No

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com