



600 Series Deadbreak T&B Catalog Number:

UPC Number:

K650-J4

Status:

78378664498

Description:

Made to Order

15/25kV 600 Series Deadbreak 4-Point Junction

Application

600 Series deadbreak elbows, straight receptacles, junctions, vault stretchers and accessories are used to connect equipment and cable on primary feeder and network circuits.

General

Temperature Range -40°C to 65°C

Technical Information

Test Point No

Specifications

Temperature Rating -40°C to 65°C

Notes

For 900-amp ratings, substitute 675 for 650 and 655; 676 for 656; K675 for K650 and K655; K676 for K656; 775 for 750 and 755; 776 for 756 and 2x for 0x in the catalog number. The 900-amp rating requires copper current-carrying connector components and copper conductor cable.

Rubber junction with stainless steel mounting plate and back plate. Add "-U" for rubber junction with stainless steel mounting plate, back plate and adjustable mounting bracket. Add "-4" for rubber junction only. Add "-5" for rubber junction, stainless steel U-straps and back plate.

Two - six-position multi-point junctions

Two - six-position multi-point junctions shown on pages H-20 - H-21

Certifications

RoHS Compliance No

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com