



**600 Series Deadbreak
T&B Catalog Number:**

UPC Number:
Status:
Description:

K656DR
78378663626
Active

15/25kV 600 Series Deadbreak Insulated Cap with Test Point (with Stud)
Application

600 Series deadbreak elbows, straight receptacles, junctions, vault stretchers and accessories are used to connect equipment and cable on primary feeder and network circuits.

General

Temperature Range -40°C to 65°C

Technical Information

Test Point Yes

Specifications

Temperature Rating -40°C to 65°C

Notes

Available without the stud by adding "N" to the catalog number.

Available with the stud factory-assembled by adding "SP" to the catalog number. 675ETP, K675ETP and 775ETP are available as -SP only. The stud is not field removable.

Available with the stud factory-assembled by adding "SP" to the catalog number. 675ETP, K675ETP and 775ETP are available as -SP only. The stud is not field removable.

Certifications

RoHS Compliance No

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com