



**600 Series Deadbreak
T&B Catalog Number:**



UPC Number:
Status:
Description:

K650BIP
78378666546
Made to Order

15/25kV 600 Series Deadbreak Insulated Plug (with Cap)

Application

600 Series deadbreak elbows, straight receptacles, junctions, vault stretchers and accessories are used to connect equipment and cable on primary feeder and network circuits.

General

Temperature Range -40°C to 65°C

Technical Information

Test Point No

Specifications

Temperature Rating -40°C to 65°C

Notes

For 900-amp ratings, substitute 675 for 650 and 655; 676 for 656; K671 for K651; K675 for K650 and K655; K676 for K656; 775 for 750 and 755; 776 for 756 and 2X for 0X in the catalog number. The 900-amp rating requires cooper current-carrying connector components and copper conductor cable.

Available with the stud factory-assembled by adding "SP" to the catalog number. 675ETP, K675ETP and 775ETP are available as -SP only. The stud is not field removable.

Available with a loose stud by adding suffix "S" to the catalog number.

Available with a loose stud by adding suffix "S" to the catalog number.

Certifications

RoHS Compliance No

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com